

Industrial Air Solutions

9600-G

The Model 9600-G is designed to accommodate a variety of sanding, metal grinding, welding, and light plasma applications. The 9600-G comes standard with four 100% polyester flame retardant filter, which cleans with 99.95% efficiency at 0.5 micron. A water pan placed over the filter helps protect it from exposure to hot sparks and extends the life of the filter. Cleaning is done by the "Jet Pulse Push Button Cleaning" that uses the compressed air inside the air tank. It releases instantly in the filters pushing the dust off and into the drawer below. Table top surface is composed of durable ¼" metal plate. A removable spark shield with hinged ends provides spark protection for area workstations. The Model 9600-G is also a great table for multiple work stations and larger applications.



9600-G

Size- 48" x 96"

Height & Weight- 36" & 1,650 lbs

Motor - 5 Hp, 1 or 3 Phase

Voltage - 220 -1Ph, or 230/460/575-3Ph

CFM - 4500

Sound Level - 80 Decibels

Spark Shield - Placement A, B, C, and D

Standard Features: Muffler, Timer, Magnehelic Gauge, Spark Shield-B, Magnetic Starter.

Options: Casters, Rubber Matting, Light Bar, Smoke Arm, Explosion Proof Motor (3 phase only), HEPA Filter Bank, Carbon Filter Bank (odor only), Aluminum Package, Spark Shield options A, C, or D

www.industrialairsolution.com
infoez@industrialairsolutions.com
Toll Free (USA) 1-877-844-3293
PO BOX 90246, Raleigh, NC 27675